

# Fast Axis Collimator

## FAC200



### Features and Advantages

Acylindrical lens for the collimation of the fast axis of diode lasers.

### Product Specifications

Specification Data	Unit	Value
Material		High-Index IR (Ohara)
Width (W)	mm	0.37 ± 0.05
Thickness (T)	mm	0.326 ± 0.01
Clear aperture	mm <sup>2</sup>	(L-0.5) × 0.27
Refractive index n @ 940 nm		> 1.9
Effective focal length (EFL) @ 940 nm	mm	0.20
Back focal length (BFL) @ 940 nm	mm	0.03
Numerical aperture (NA)		0.8
Transmission	%	> 99
Power within an angle of ± 3.3 mrad <sup>(1)</sup>	%	> 85

Product Code	ZLE001774 <sup>(3)</sup>	ZLE002137 <sup>(3)</sup>	ZLE002097 <sup>(3)</sup>	ZLE002142 <sup>(3)</sup>	
<b>Specification Data</b>	<b>Unit</b>	<b>Value</b>			
Length (L)	mm	3.15 ± 0.05	4.0 ± 0.05	3.15 ± 0.05	4.0 ± 0.05
AR-Coating	nm	900 - 1000	790 - 990	600 - 700	785 - 810
Surface imperfections (DIN ISO 10110-7)		5/2x0.025; C2x0.1; L2x0.025; E <sup>(2)</sup>	5/3x0.025; C3x0.1; L3x0.025; E <sup>(2)</sup>	5/2x0.025; C2x0.1; L2x0.025; E <sup>(2)</sup>	5/3x0.025; C3x0.1; L3x0.025; E <sup>(2)</sup>

<sup>(1)</sup> Valid for an emitter-height of 1 µm and no smile of the laser diode.

<sup>(2)</sup> Chipping on short edge 0.2, chipping on long edge 0.08.

<sup>(3)</sup> Example for customization – design, dimensions & coatings on request.

### Product Drawing (mm)

